


PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF
 CAPSTAN AG INC. ANY REPRODUCTION IN PART OR AS A WHOLE
 WITHOUT WRITTEN PERMISSION OF CAPSTAN AG INC IS PROHIBITED

REV	ECR	DESCRIPTION	DATE	BY
A		Production Release	8/17/12	BLS
B	1052	Added 1.5" Unbraided Dimension	5/26/15	BLS




(B) V9B	⑤	①	V9A	Blue/Orange (A)
(B) V8B	④	②	V8A	Black/Orange (A)
(B) V7B	③	③	V7A	Red/Orange (A)
(B) V6B	②	④	V6A	Brown/White (A)
(B) V5B	①	⑤	V5A	Green/White (A)
(B) V4B	⑥	⑥	V4A	Yellow/White (A)
(B) V3B	⑦	⑦	V3A	Blue/White (A)
(B) V2B	⑧	⑧	V2A	Black/White (A)
(B) V1B	⑨	⑨	V1A	Red/White (A)

Add Dielectric Grease, Dow Corning 4 Electrical
 Insulating Compound, to Terminal Side of Connector.

Notes:

- Wire cut Lengths Determines Final Part Length.
- Strip and Braid Length Per Manufactures Preference.

16	708000-015	Braiding, Black	.274
15	708000-176/9	Wire, 18 Ga, Red/White	68
14	708000-177/9	Wire, 18 Ga, Black/White	108
13	708000-178/9	Wire, 18 Ga, Blue/White	148
12	708000-182/9	Wire, 18 Ga, Yellow/White	188
11	708000-174/9	Wire, 18 Ga, Green/White	228
10	708000-179/9	Wire, 18 Ga, Brown/White	268
9	708000-176/3	Wire, 18 Ga, Red/Orange	308
8	708000-177/3	Wire, 18 Ga, Black/Orange	348
7	708000-178/3	Wire, 18 Ga, Blue/Orange	388
6			
5	706530-251	Connector, Receptical, 18 Pin	1
4	706530-253	Terminal, Socket, 18-22 Ga	18
3	706530-205	Terminal, Male, 18-20 Ga	18
2	706500-001	Seal, Cable, Green, 16-18 Ga	18
1	706510-502	Shroud, 2 Pin	9

Item	Part Number	Description	Qty	
UNLESS OTHERWISE SPECIFIED:		<div> CAPSTAN Ag Systems, Inc.</div> <div>CAPSTAN AG SYSTEMS, INC. 101 N. KANSAS AVE., TOPEKA, KS 66603</div>		
DIMENSIONS ARE IN INCHES				
TOLERANCES:				
FRACTIONAL ±				
ANGULAR: MACH ± BEND ±				
TWO PLACE DECIMAL ±				
THREE PLACE DECIMAL ±				
INTERPRET GEOMETRIC TOLERANCING PER:				
MATERIAL				
FINISH				
DO NOT SCALE DRAWING				
		SIZE B	DWG No: <div>118200-129</div>	REV B
		SCALE: None		SHEET 1 of 1