

Long Term Stability, +/- 0.25% Operating Temp., -40F to 215F Compensated Range -4F to 185F Total Error Band EMI/RFI Protected, CE Mark UL Listed

			DEV		DEAGDIDEIGNI			DY/
			REV C	Dedrey	DESCRIPTION vn in SolidWorks	DA1 3/5/		BY BLS
				L			-	
L L								
$\geq$								
$\langle A \rangle$								
	×.							
22 M								
	C							
hite		-						
əd		7)						
ack								
·	1							
	1							
	I							
	1							
7	706500-0				d 20-22 Ga			3
6	706530-2	05	Termina	al, Male,	d 20-22 Ga 18-20 Ga			3
6 5	706530-20 706510-50	05 03	Termina Shroud,	al, Male, , 3-Pin	18-20 Ga			3 1
6 5 4	706530-20 706510-50 620201-10	05 03 00	Termina Shroud, TUBE, S	al, Male, , 3-Pin Shrink, <i>*</i>	18-20 Ga I/4" x 1-1/4" Lg, Red			3 1 1
6 5 4 3	706530-20 706510-50 620201-10 716008-30	05 03 00 01	Termina Shroud, TUBE, S Fitting, S	al, Male, , 3-Pin Shrink, 1 3/8 Nylo	18-20 Ga I/4" x 1-1/4" Lg, Red n, Straight Flex			3 1 1 1
6 5 4 3 2	706530-20 706510-50 620201-10 716008-30 716008-30	05 03 00 01 02	Termina Shroud, TUBE, S Fitting, S Bushing	al, Male, , 3-Pin Shrink, 1 3/8 Nylo g, 3/4 Ml	18-20 Ga I/4" x 1-1/4" Lg, Red n, Straight Flex PT x 3/8 FPT, Poly			3 1 1 1 1
6 5 4 3 2 1	706530-20 706510-50 620201-10 716008-30 716008-30 706702-2	05 03 00 01 02 50	Termina Shroud, TUBE, S Fitting, S Bushing	al, Male, , 3-Pin Shrink, 3/8 Nylo g, 3/4 Ml e Senso	18-20 Ga //4" x 1-1/4" Lg, Red n, Straight Flex PT x 3/8 FPT, Poly or 250 psi			3 1 1 1 1 1 1
6 5 4 3 2 1 <b>Item</b>	706530-20 706510-50 620201-11 716008-30 716008-30 706702-20 <b>Part Num</b>	05 03 00 01 02 50	Termina Shroud, TUBE, S Fitting, S Bushing	al, Male, , 3-Pin Shrink, 3/8 Nylo g, 3/4 Ml e Senso	18-20 Ga I/4" x 1-1/4" Lg, Red n, Straight Flex PT x 3/8 FPT, Poly			3 1 1 1 1
6 5 4 3 2 1 <b>Item</b>	706530-20 706510-50 620201-10 716008-30 716008-30 706702-2	05 03 00 01 02 50 <b>1ber</b>	Termina Shroud, TUBE, S Fitting, S Bushing Pressur	al, Male, , 3-Pin Shrink, ^ 3/8 Nylo g, 3/4 MI e Senso	18-20 Ga I/4" x 1-1/4" Lg, Red n, Straight Flex PT x 3/8 FPT, Poly or 250 psi <b>Description</b>	STEMS		3 1 1 1 1 1 <b>Qty</b>
6 5 4 3 2 1 <b>Item</b> UNLESS O' DIMENSION	706530-20 706510-50 620201-11 716008-30 716008-30 716008-30 706702-20 Part Num THERWISE SPECIFIED: NS ARE IN INCHES	05 03 00 01 02 50 <b>1ber</b>	Termina Shroud, TUBE, S Fitting, S Bushing Pressur	al, Male, , 3-Pin Shrink, 3/8 Nylo g, 3/4 MI re Senso	18-20 Ga I/4" x 1-1/4" Lg, Red n, Straight Flex PT x 3/8 FPT, Poly or 250 psi Description CAPSTAN AG SY		NC	3 1 1 1 1 1 2 Qty
6 5 4 3 2 1 <b>Item</b> UNLESS O DIMENSION TOLERANCC FRACTION	706530-20 706510-50 620201-10 716008-30 716008-30 706702-20 <b>Part Num</b> THERWISE SPECIFIED: NS ARE IN INCHES ZES: AL ±	05 03 00 01 02 50 <b>1ber</b>	Termina Shroud, TUBE, S Fitting, S Bushing Pressur APSTA g Systems, Inc	al, Male, , 3-Pin Shrink, <sup>2</sup> 3/8 Nylo g, 3/4 MI re Senso Senso 101	18-20 Ga I/4" x 1-1/4" Lg, Red n, Straight Flex PT x 3/8 FPT, Poly or 250 psi Description CAPSTAN AG SY N. KANSAS AVE., T		NC	3 1 1 1 1 1 2 Qty
6 5 4 3 2 1 UNLESS O DIMENSION TOLERANC FRACTION/ ANGULAR:	706530-20 706510-50 620201-10 716008-30 716008-30 706702-20 <b>Part Num</b> THERWISE SPECIFIED: NS ARE IN INCHES CES:	05 03 00 01 02 50 <b>1ber</b>	Termina Shroud, TUBE, S Fitting, S Bushing Pressur APSTAN g Systems, Ind Name	al, Male, , 3-Pin Shrink, 7 3/8 Nylo 3/8 Nylo 3/4 Ml c Senso N 101	18-20 Ga I/4" x 1-1/4" Lg, Red n, Straight Flex PT x 3/8 FPT, Poly or 250 psi Description CAPSTAN AG SY N. KANSAS AVE., T	OPEKA, K	NC S 60	3 1 1 1 1 1 2 Qty
6 5 4 3 2 1 <b>Item</b> UNLESS O DIMENSION TOLERANC FRACTION, ANGULAR: TWO PLAC THREE PLAC	706530-20   706510-50   620201-11   716008-30   716008-30   706702-20   Part Num   THERWISE SPECIFIED:   NS ARE IN INCHES   ESS:   AL±   EDECIMAL ±   CE DECIMAL ±	05 03 00 01 02 50 <b>ber</b> C	Termina Shroud, TUBE, S Fitting, S Bushing Pressur APSTAN g Systems, Ind Name	al, Male, , 3-Pin Shrink, <sup>2</sup> 3/8 Nylo 3/8 Nylo 3/4 Mf re Sensc 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	18-20 Ga I/4" x 1-1/4" Lg, Red n, Straight Flex PT x 3/8 FPT, Poly or 250 psi Description CAPSTAN AG SY N. KANSAS AVE., T ITTLE: Pressure Sens	OPEKA, K	NC S 60	3 1 1 1 1 1 2 Qty
6 5 4 3 2 1 <b>Item</b> UNLESS O DIMENSION TOLERANC FRACTION, ANGULAR: TWO PLAC THREE PLAC	706530-20   706510-50   620201-11   716008-30   716008-30   706702-20   Part Num   DTHERWISE SPECIFIED:   NS ARE IN INCHES   250   PACH ±   26 DECIMAL ±   27 DECIMAL ±   26 DECIMAL ±   26 DECIMAL ±   27 DECIMAL ±   26 DECIMAL ±	05 03 00 01 02 50 <b>ber</b> C	Termina Shroud, TUBE, S Fitting, S Bushing Pressur APSTAN g Systems, Ind Name	al, Male, , 3-Pin Shrink, <sup>2</sup> 3/8 Nylo 3/8 Nylo 3/4 Mf re Sensc 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	18-20 Ga I/4" x 1-1/4" Lg, Red n, Straight Flex PT x 3/8 FPT, Poly or 250 psi Description CAPSTAN AG SY N. KANSAS AVE., T	OPEKA, K	NC S 60	3 1 1 1 1 1 2 Qty
6 5 4 3 2 1 UNLESS O DIMENSION TOLERANC FRACTION, ANGULAR: TWO PLAC THREE PLAC INTERPRET C	706530-20   706510-50   620201-11   716008-30   716008-30   706702-20   Part Num   DTHERWISE SPECIFIED:   NS ARE IN INCHES   250   PACH ±   26 DECIMAL ±   27 DECIMAL ±   26 DECIMAL ±   26 DECIMAL ±   27 DECIMAL ±   26 DECIMAL ±	05 03 00 01 02 50 <b>ber</b> <u>1</u> 02 50 <b>ber</b> C Drawn	Termina Shroud, TUBE, S Fitting, S Bushing Pressur APSTAN g Systems, Ind Name	al, Male, , 3-Pin Shrink, <sup>~</sup> <u>3/8 Nylo</u> g, 3/4 MI re Sensc <sup>N</sup> . <b>101</b> Date 7/3/12	18-20 Ga I/4" x 1-1/4" Lg, Red n, Straight Flex PT x 3/8 FPT, Poly or 250 psi Description CAPSTAN AG SY N. KANSAS AVE., T ITTLE: Pressure Sens 250 psi, 1/4" M SIZE DWG №:	OPEKA, K sor Assemi INPT	NC S 60	3 1 1 1 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
6 5 4 3 2 1 UNLESS O DIMENSION TOLERANC FRACTION, ANGULAR: TWO PLAC THREE PLAC INTERPRET O TOLERANC	706530-20   706510-50   620201-11   716008-30   716008-30   706702-20   Part Num   DTHERWISE SPECIFIED:   NS ARE IN INCHES   250   PACH ±   26 DECIMAL ±   27 DECIMAL ±   26 DECIMAL ±   26 DECIMAL ±   27 DECIMAL ±   26 DECIMAL ±	05 03 00 01 02 50 <b>ber</b> <u>1</u> 02 50 <b>ber</b> C Drawn	Termina Shroud, TUBE, S Fitting, S Bushing Pressur APSTAN g Systems, Ind Name	al, Male, , 3-Pin Shrink, <sup>~</sup> <u>3/8 Nylo</u> g, 3/4 MI re Sensc <sup>N</sup> . <b>101</b> Date 7/3/12	18-20 Ga I/4" x 1-1/4" Lg, Red n, Straight Flex PT x 3/8 FPT, Poly or 250 psi Description CAPSTAN AG SY N. KANSAS AVE., T ITTLE: Pressure Sens 250 psi, 1/4" M SIZE DWG №:	OPEKA, K	NC S 60	3 1 1 1 1 Qty 5603
6 5 4 3 2 1 UNLESS O DIMENSION TOLERANC FRACTION/ ANGULAR: TWO PLAC TOLERANC INTERPRET ( TOLERANC THREE PLAC	706530-20   706510-50   620201-11   716008-30   716008-30   706702-20   Part Num   DTHERWISE SPECIFIED:   NS ARE IN INCHES   250   PACH ±   26 DECIMAL ±   27 DECIMAL ±   26 DECIMAL ±   26 DECIMAL ±   27 DECIMAL ±   26 DECIMAL ±	05 03 00 01 02 50 <b>ber</b> <u>1</u> 02 50 <b>ber</b> C Drawn	Termina Shroud, TUBE, S Fitting, S Bushing Pressur APSTAN g Systems, Ind Name	al, Male, , 3-Pin Shrink, 7 3/8 Nylo 3/8 Nylo 3/4 MI re Senso <b>101</b> Date 7/3/12	18-20 Ga I/4" x 1-1/4" Lg, Red n, Straight Flex PT x 3/8 FPT, Poly or 250 psi Description CAPSTAN AG SY N. KANSAS AVE., T TITLE: Pressure Sens 250 psi, 1/4" M SIZE DWG №: CAPSTA	орека, к sor Assem INPT 20-250	bly,	3 1 1 1 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0